

3M™ DBI-SALA® ExoFit™ XE50 Positioning Safety Harness with quick connect buckles

Part number(s):

1112714 (Size 1) 1112715 (Size 2) 1112716 (Size 3)

Description

Sub-brand:	DBI-SALA®
Industry:	Construction, General Industrial, General Manufacturing, Transportation
Applications:	Climbing, Positioning

Features

Features		
Rear fall arrest attachment point:	Large D-ring Steel - zinc plated	
Front fall arrest attachment point:	Standard D-ring Steel - zinc plated	
Work positioning Attachment points:	Large cranked D-ring Steel - zinc plated	
Leg Buckles:	Quick connectSteel - zinc plated/black paint	
Chest Buckles:	Quick connect Steel - zinc plated/black paint, aluminium - grey anodisation	
Waist Buckles:	Quick connectSteel - zinc plated/black paint	
Adjustment:	Legs, waist, torsoTorso: Revolving adjusterSteel/aluminium - ratchet buckle	
Webbing:	45mm Polyester - Scotchgard™	
Thread:	Polyester	
Additional features:	 Front & rear fall indicators Waist padding 2x Auto-resetting/repositionable lanyard keepers RFID Equipped Suspension trauma straps Dedicated personal self-retracting lifeline attachment point 	
Weight capacity:	140 kg	
Standards:	CE EN361:2002; EN358:2019UKCA	




Front



Back

3M™ DBI-SALA® Fall Arrest Harness sizing chart



Weight

	∢ ····≻	kg
1112714	Size 1	2.46
1112715	Size 2	2.53
1112716	Size 3	2.60



Important notice

The mounting and use of the product described within this document assumes that the user has previous experience of this type of product and that it will be assembled by a competent professional according to product documentation. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected application.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M Group (who cannot verify or control these elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for products are determined with the sales contract documents and with the mandatory and applicable law, excluding any other warranty or compensation.



