



DBI-SALA® ROLLGLISS R350

AG6350ST31/30

- 3:1 reduction
- 30 m rope length
- 7.5 m useful rope length
- Working load max: 150kg (1 person)
- Weight 5.7kg



AG6350ST21/50

- 2:1 reduction
- 50 m rope length
- 16 m useful rope length
- Working load max: 150kg (1 people)
- Weight 4kg



AG6350ST31/60

- 3:1 reduction
- 60 m rope length
- 15 m useful rope length
- Working load max: 150kg (1 person)
- Weight 6.2kg



AG6350ST51/60

- 5:1 reduction
- 60 m rope length
- 10 m useful rope length
- Working load max: 250kg (2 people)
- Weight 6.4kg



CE Comply with standards
EN 341 class A et EN 1496 class B

Top/R350

- Flanges : anodised aluminium
- Lateral protection : composite material
- Rope drum : teflon covered aluminium
- Including device to adapt pulley
- Diameter: 160 mm

Fixed and running pulley

- Flanges : anodised aluminium
- Pulley : composite material

Rope

- White braided
- Diameter 9 mm
- Polyamide
- Breaking strength > 1200 daN
- Weight/meter : 50 g/m

Hooks

- 2 x Twist Lock Carabiners
- Strength > 2500 daN
- Opening : 18 mm
- High strength steel electro zinc plated

Net weight

- 1.75 kg (just device)



Capital Safety Group, EMEA | www.capitalsafety.com | information@capitalsafety.com

5a Merse Road, North Moons Moat,
Redditch, Worcestershire B98 9HL
t: +44 (0) 1527 548 000 f: +44 (0) 1527 591 000

Le Broc Center, Z.I. 1ère avenue, BP 15
06511 Carros le Broc Cedex France
t: +33 (0)497 100 010 f: +33 (0)493 087 970

