


Universe	Professional
Type	Verticality
Category	Harnesses
Subcategory	Rope access harnesses



ASTRO® BOD FAST international version

With an integrated CROLL L ventral rope clamp, the ASTRO BOD FAST harness is designed for greater efficiency and comfort during rope ascents. The gated ventral attachment point allows optimal integration of equipment (rope clamp, seat...). Wide, semi-rigid waistbelt and leg loops give excellent support. They are contoured and lined with breathable foam padding for comfort when suspended. The DOUBLEBACK self-locking buckles at the rear of the harness, between the waistbelt and the leg loops, allow for a shorter adjustment when the dorsal attachment point is used. The harness also facilitates the carrying and organizing of work tools, with multiple equipment loops and retainers for attaching CARITool tool holders and TOOLBAG tool-holder pouches. It has a fall indicator on the dorsal attachment point and is certified to North American and European standards. ASTRO BOD FAST international version features leg loops with FAST automatic buckles.



The gated ventral attachment point allows optimal integration of equipment (rope clamp, lanyard, seat...).



Two metallic side attachment points allow easy connection of equipment and can be folded down to prevent them snagging accidentally when not in use.



The shoulder straps are equipped with a FAST automatic buckle to facilitate harness donning.



Fall indicator on the dorsal attachment point: a red strap appears on the dorsal attachment point after a fall to indicate that the harness should be retired.

Short Description Ultra-comfortable rope access harness

Selling Points



- Gated ventral attachment point can be opened for optimal integration of equipment:
 - connection of CROLL ventral rope clamp on the ventral point for greater efficiency on rope ascents
 - PROGRESS lanyard connects directly on the ventral attachment point
 - connection of the PODIUM seat on the axle of the attachment point allows the load to be supported directly by the descender, while guaranteeing mobility at the ventral attachment point
- Ultra-comfortable design:
 - semi-rigid, wide waistbelt and leg loops for excellent support; sculpted and lined with breathable foam padding for comfort during suspension
 - foam shoulder straps are widely spaced to reduce neck chafing. When the waistbelt is loaded, they help distribute the load over the shoulders
 - metallic side attachment points allow easy connection of equipment and can be folded down to prevent them snagging accidentally when not in use
- Convenient adjustment:
 - waistbelt and shoulder straps equipped with self-locking DOUBLEBACK buckles for quick and easy adjustment
 - leg loops and shoulder straps equipped with FAST automatic buckles to facilitate harness donning; quick and easy fastening and unfastening, without loss of adjustment, even with gloves on
 - DOUBLEBACK self-locking buckles at the rear of the harness, between the waistbelt and the leg loops, allow for an adjustment for use on the dorsal attachment point. In case of a fall on this point, a shorter adjustment allows the weight to be taken up on the leg loops so that the user may remain more comfortably suspended while awaiting rescue
- Facilitates carrying and organization of tools:
 - six pre-shaped equipment loops with protective sheath
 - two slots for CARITool tool holder
 - two slots for TOOLBAG tool pouch
- The international version has a fall indicator: a red strap appears on the dorsal attachment point after a fall to indicate that the harness should be retired

Specification

- Ventral attachment point: connection of a descender, a positioning lanyard for use in single mode, a progression lanyard, and a seat
 - Lateral attachment points: attachment for a positioning lanyard for use in double mode
 - Sternal attachment point: fall arrest system attachment
 - Dorsal attachment point: fall arrest system attachment
 - Rear attachment point on the waistbelt: restraint lanyard attachment
 - Certification(s): ANSI Z359.11, NFPA 1983 classe III, CSA Z259.10, CE EN 361, CE EN 358, CE EN 813, CE EN 12841 type B
 - Material(s): nylon, polyester, aluminum, steel
-

Specifications by reference

Reference(s)	C083BA00	C083BA01	C083BA02	C083BA03
				
Color(s)	black/yellow	black/yellow	black/yellow	black
Size	0	1	2	0
Waist belt	65-80 cm	70-93 cm	83-120 cm	65-80 cm
Leg loops	44-59 cm	47-62 cm	50-65 cm	44-59 cm
Stature	160-180 cm	165-185 cm	175-200 cm	160-180 cm
Weight	2480 g	2530 g	2620 g	2480 g
Made in	RO	RO	RO	RO
Guarantee	3 years	3 years	3 years	3 years
Packing	1	1	1	1
Case quantity	3	3	3	3
EAN	3342540826977	3342540826960	3342540826946	3342540826939

Reference(s)	C083BA04	C083BA05
		
Color(s)	black	black
Size	1	2
Waist belt	70-93 cm	83-120 cm
Leg loops	47-62 cm	50-65 cm
Stature	165-185 cm	175-200 cm
Weight	2530 g	2620 g
Made in	RO	RO
Guarantee	3 years	3 years
Packing	1	1
Case quantity	3	3
EAN	3342540826915	3342540826908

Accessory(ies) Shackles
TOOLBAG
CARITool

Related product(s) PODIUM
RIG
ASAP® LOCK
ASAP'SORBER AXESS
GRILLON