

01/10/

PRODUCT DATA SHEET

K'biner alu 12mm offset, tri-act, eye

CKA61

Triple lock captive eye karabiner

Features:

- Aluminium Alloy
- Anodised
- Triple Action
- Gate Opening: 22mm
- Overall Size: L 140mm, W 84mm, Ø 16mm
- Captive eye

Aluminium alloy for reduced weight.

Anodised for corrosion protection.

Captive eye for permanent (e.g. lanyards) or semi-permanent assemblies.

Captive eye keeps the loading close to the spine (thus reducing any loss in strength).

Triple action gate is self closing and locking and allows one handed operation. To open gate requires 3 separate actions, virtually eliminating the risk of accidental opening.



Specifications:

NB: specifications and colour may change without notice.

Size: L 140mm, W 84mm, Ø 16mm, captive eye Ø 22mm

EN Test Mass: n/a

Loading: 28kN major axis

Conformity: CE EN362:2004/T

Materials: Anodised Aluminium Alloy

Weight (kg): 0.12

Industries: Used in all work at height industries and rescue

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: admin@heightec.com

heightec.com