

ASTRA K'biner, steel, offset, twistlock, captive bar

CKS3

Twistlock karabiner offset D with optional captive bar

Features:

- Steel
- Zinc plated
- Twistlock
- Gate Opening: 22mm
- Overall Size: L 111mm, W 70mm, Ø 11mm
- Offset 'D'
- Optional Captive bar

Steel for strength.

Zinc plated for corrosion protection.

Twistlock gate is self closing and locking and allows one handed operation.

Supplied with separate captive bar which can be fitted by the user if required.

The captive bar is used to fix the karabiner to the rope etc. to prevent loss or disassembly. It also keeps the loading close to the spine (thus reducing any loss in strength).

Also available alternative gate types:

- CKS2 - Screwgate
- CKS4 - Triple Action



Specifications:

NB: specifications and colour may change without notice.

Size: L 111mm, W 70mm, Ø 11mm

EN Test Mass: n/a

Loading: 45kN major axis

Conformity: EN362:2004/B

Materials: Zinc plated steel

Weight (kg): 0.21

Industries: Used in all work at height industries and rescue

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: admin@heightec.com

heightec.com

PDS64

10/02/22