

PHOENIX rescue harness QC

H11Q

Designed for fire and industrial rescue teams working in confined space, vertical rescue and fall arrest. Suitable for use with back-mounted breathing apparatus.

Features:

- Quick fit buckles for speed of fit
- Highly durable and comfortable to wear
- Integral back panel
- Semi-circular screwlink front attachment point
- High rear attachment point
- Protected leg loops
- Adjustable locking side buckles
- Captive buckles with large tabs
- Low profile accessory loop at shoulder

Integral back panel helps to maintain the structure of the harness.

Semi-circular screwlink permits safe multi-directional loading for casualty attachment.

Front attachment point is rated for fall arrest, it can be used for lowering or raising and suspension.

Rear attachment point is rated for fall arrest and suspension, it is positioned high to be compatible with breathing apparatus and is reachable by the user.

Double thickness webbing provides added protection and wear resistance for the leg loops.

Adjustable side buckles allow for added comfort and sizing, but lock to prevent accidental release.

Leg loops have quick connect buckles for fast donning.

Buckles are captive to prevent disassembly.

Parking point allows attachment of lanyard, torch, radio etc



NB: specifications and colour may change without notice.

Specifications:

Size: Universal	Attachment Points:
EN Test Mass: 150kg	Dorsal
	Sternal
Loading: Fall Arrest & Rescue loads	
Conformity: EN361, EN1497	Harness Measurements (cm):
	Torso 95-130
Materials: Polyamide, Stainless Steel and Plated screwlink.	Waist -
	Thigh 65-110
Weight (kg): 1.16	
Industries: Fire and rescue service. Can be used as part of both fall arrest and suspension systems.	

PHOENIX rescue harness QC, Red

H11QR

Designed for fire and industrial rescue teams working in confined space, vertical rescue and fall arrest. Suitable for use with back-mounted breathing apparatus.

Features:

- Quick fit buckles for speed of fit
- Highly durable and comfortable to wear
- Integral back panel
- Semi-circular screwlink front attachment point
- High rear attachment point
- Protected leg loops
- Adjustable locking side buckles
- Captive buckles with large tabs
- Low profile accessory loop at shoulder

Integral back panel helps to maintain the structure of the harness.

Semi-circular screwlink permits safe multi-directional loading for casualty attachment.

Front attachment point is rated for fall arrest, it can be used for lowering or raising and suspension.

Rear attachment point is rated for fall arrest and suspension, it is positioned high to be compatible with breathing apparatus and is reachable by the user.

Highly-durable Cordura sleeves provide added protection and wear resistance for the leg loops.

Adjustable side buckles allow for added comfort and sizing, but lock to prevent accidental release.

Buckles are captive to prevent disassembly and with large tabs for easy adjustment even wearing gloves.

Accessory D-loop allows attachment of torch, radio etc

Options:

H11 - Standard leg loops



NB: specifications and colour may change without notice.

Specifications:

Size: Universal	Attachment Points:
EN Test Mass: 150kg	Dorsal Sternal
Loading: Fall Arrest & Rescue loads	
Conformity: EN361, EN1497	Harness Measurements (cm):
Materials: Polyamide, Stainless Steel and Plated screwlink.	Torso 95-130
Weight (kg): 1.16	Waist -
Industries: Fire and rescue service. Can be used as part of both fall arrest and suspension systems.	Thigh 65-110