

Pulsar handled ascender

D40

Rope access handled ascender, incorporating X-Cam™

Features:

- X-Cam technology
- Ergonomic handle position and profile
- Two attachment points
- High strength & durable construction

X-Cam has a more advanced tooth design than traditional cams and is more suitable for industrial applications as it does not pluck the rope, so reducing rate of rope wear.

In tests on 11mm Tectra the average breaking load is around 675 kg for X-cams versus 535 kg for established sharp toothed design.

X-cam geometry has been developed to address a number of issues:

- Does not jam, even against knots
- Provides high degree of grip on ropes of varying condition including after rupture of sheath
- Highly effective on angled ropes
- Facilitates down-climbing

Handle design is ergonomically positioned and profiled for optimal pulling and greater comfort.

Two attachment points allow cowstail and footloop to be connected separately which eliminates the need to open a loaded karabiner.

The materials and design used in construction have been selected to provide high strength and durability needed for industrial applications. Each device is individually numbered making equipment management easier.

Option:

D40L - Left-handed



NB: specifications and colour may change without notice.

Specifications:

Size: 9mm - 13mm rope

EN Test Mass: 125kg

Loading: Not Applicable

Conformity: EN567, EN12841(B)

Materials: Aluminium, stainless steel and nylon

Weight (kg): 0.24

Industries: Rope Access