

Products, training and operational support services for professional work at height and rescue

## DUON & DUON Air Helmet

MH01-02

High specification helmets suitable for work at height with dual certification, meeting both 'industrial' and 'mountaineering' standards.

MH01 DUON™ (unvented - not shown) - EN397 MM, 440 V a.c.  
MH02 DUON Air™ - EN397, EN12492 (variable configuration)

### Performance

EN397 ('industrial') weak chinstrap allows release if the helmet becomes trapped. Small vents (no vents in Duon MH01) prevent items such as sparks hitting the wearer.

EN12492 ('mountaineering') strong chinstrap so the helmet stays in place in a fall. Large vents to enable air to circulate.

Hazards change so why doesn't your helmet?

DUON helmets have a unique patented chinstrap buckle which can be switched between 'strong' and 'weak' to give conformity with either standard. The vents in the DUON-Air can also be switched to give conformity with either standard. All switching is carried out without tools.

**Compatibility:** 'T-slot' side fittings for standard ear defenders etc. Clips for elastic strap mounted lights, cameras etc. Brackets front and rear for popular cap lamps and other accessories.

**Comfort:** Primary adjustment by ratchet wheel, can be operated with one hand even whilst being worn. Secondary adjustment to small/medium/large helps keep the helmet centred on the head. Headband height adjustment allows user to maintain field of view. 6 point head cradle for stability.

**Colour Options:** White, Green, Orange (others subject to qty)

**Accessories:** Ear defenders, visor, headtorch, replacement sweatbands/pads, Bespoke marketing/company logo's.



Patented GB2531146

### Specifications:

<b>Size:</b>	52cm to 66cm circumference
<b>Materials:</b>	ABS, Nylon and Polyester
<b>EN test Mass:</b>	
<b>Loading:</b>	
<b>Weight (kg):</b>	0.45
<b>Conformity:</b>	EN397 and EN12492
<b>Markets:</b>	Used in all work at height and rescue

Specifications may change without notice.