

ELITE twin l'yrd - tri-act, 1.60m, CE/ANSI hooks

L2T160A

High load rated energy absorbing lanyard with alloy locking connectors.

Features:

- High load rating, approved for users up to 140kg.
- Durable protective cover
- Suspension intolerance relief loops
- High twist HELIX™ ropes
- Large central ring
- Unique serial ID number

Alloy locking connectors with 60mm opening and 16kN cross gate strength.

Heatshrunk absorber with replaceable cover, tamper evident but with increased durability.

Suspension intolerance relief loop deploys automatically providing support for both feet.

Absorber will not deploy at force less than 200kg. Min. strength 1500kg after deployment.

Patented HELIX™ ropes allow high degree of twist in lanyard legs, minimising kinking.

Large central ring provides parking point for unused leg and prevents issues caused by 3 way loading.

Unique serial ID number allows easy management of equipment.

Approved for users up to 140kg.

Options: 1.25m, 1.60m, 1.75m lengths



Specifications:

NB: specifications and colour may change without notice.

Size: 1.25m, 1.60m, 1.75m lengths

EN Test Mass: 100kg

Loading: Additionally tested 140kg Fall factor 2

Conformity: EN354:2010, EN355:2002, EN362:2004

Materials: Polyester / polyamide webbing. Alloy connectors.

Weight (kg): 2.05

Industries: Renewables (Wind)

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: admin@heightec.com

heightec.com

PDS1355

15/03/22