

COMPACT LADDER

Part of the flexible sided ladder range from Lyon Equipment

The COMPACT LADDER is a general purpose flexible sided ladder for applications such as manhole entry or access to a lighting truss.

Featuring aluminium alloy rungs and flexible wire galvanised wire rope sides, the Lyon COMPACT LADDER is ideal when you need to keep weight down, whilst maintaining loading capacity

[See overleaf for detailed product features](#)



| CODE | | LENGTH | RUNG SPACING MATERIALS | |
|---|----------------------|--------|------------------------|-----------------------------------|
| Compact - 4mm galvanised steel wire side - 12.5mm plain aluminium alloy rungs 150mm wide | | | | |
| LO 4 05 25 | Swaged Eye Fittings | 5mtrs | 25cm | Galvanised steel with plain rungs |
| LO 4 05 30 | | 5mtrs | 30cm | |
| LO 4 10 25 | | 10mtrs | 25cm | |
| LO 4 10 30 | | 10mtrs | 30cm | |
| LM 4 05 25 | Maillon End Fittings | 5mtrs | 25cm | Galvanised steel with plain rungs |
| LM 4 05 30 | | 5mtrs | 30cm | |
| LM 4 10 25 | | 10mtrs | 25cm | |
| LM 4 10 30 | | 10mtrs | 30cm | |

| | | | | |
|---|----------------------|--------|------|-----------------------------------|
| Compact Lightweight - 3mm Galvanised Steel Wire Side - 12.5mm Plain Aluminium Alloy Rungs 150mm wide - Not recommended for intensive use | | | | |
| LO 3 05 25 | Swaged Eye Fittings | 5mtrs | 25cm | Galvanised steel with plain rungs |
| LO 3 05 30 | | 5mtrs | 30cm | |
| LO 3 10 25 | | 10mtrs | 25cm | |
| LO 3 10 30 | | 10mtrs | 30cm | |
| LM 3 05 25 | Maillon End Fittings | 5mtrs | 25cm | Galvanised steel with plain rungs |
| LM 3 05 30 | | 5mtrs | 30cm | |
| LM 3 10 25 | | 10mtrs | 25cm | |
| LM 3 10 30 | | 10mtrs | 30cm | |

At Lyon Equipment, we design, manufacture and supply high quality and innovative, adventure, work at height and specialist rescue equipment - delivering expert advice on all our products and their applications





Product features:

- The compact design allows easy storage and transport
- Lighter weight than wide rung ladders
- Available with two side wire options: 3mm galvanised / 4mm galvanised
- Choice of rung spacings: 25 or 30cm
- 5 or 10mtr standard lengths - lengths of up to 20mtrs available to special order
- Easily joined together if necessary

Sides

Regular wire -

the most popular style - durable and versatile. Recommended for frequent use. Uses 4mm wire.

Lightweight wire -

for situations where weight is more important than durability. Only recommended for infrequent use. Uses 3mm wire.

Rungs

Plain alloy -

plain aluminium alloy rung. The standard for most applications.

End Fitting options:



Maillon



Swaged Eye

For complete user instructions please visit www.lyon.co.uk/user-instructions

Lyon Equipment provide other ladder solutions - to learn more about our products and the services we offer please visit www.lyon.co.uk



Lyon Equipment Limited
Unit 3-7, Tebay Business Park,
Old Tebay, Penrith, Cumbria,
CA10 3SS, UK
Company number 3107118
Registered in England & Wales.

venture further

