

Rotor Tower Crane Rescue System 50m

WK39

Self contained rescue system for self-evacuation or recovery of a casualty from tower cranes

Designed to allow automatic self-evacuation giving limited maximum descent speed, or allow the controlled rescue of a casualty from a tower crane cab, jib or ladder by lowering or lifting.

This kit complies with the Construction Plant-hire Association (CPA) guidance regarding rescue from Tower Cranes (TIN013).

The locking extendable rescue pole extends up to 3.5m and allows immediate connection to the harness of a person hanging suspended after a fall.

The pulley provides mechanical advantage to raise a load or deviate a rope.

Includes the ultra compact, universal sized, casualty harness. Lightweight and easy to fit to an incapacitated casualty.

This compact system comes complete with durable KARI bag.

Kit includes:

- Rotor CRD x 1
- 9.5mm CRD Rope x 1
- Delta casualty harness x 1
- Rescue reach pole x 1
- Rescue pulley x1
- Throwline, 50m x 1
- Sling, nylon protected 120cm x 2
- Oval karabiner x 3
- Oval captive karabiner x 1
- Pear screwlink x 1
- Rescue kit bag x 1

Available in 50m or 100m.



Patented GB2515341

Specifications:

NB: specifications and colour may change without notice.

Size: 50m

EN Test Mass:

Loading:

Conformity: Various EN Approvals

Materials: Various

Weight (kg): 15.00

Industries: Tower Crane, Construction

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: admin@heightec.com

heightec.com

PDS380

10/02/22